




Water-based Polyurethane Prefinish



Natural Oil Prefinish



Oil-based Polyurethane On-Site Finish



Unfinished

Ant. APPEARANCE-GRADE RESAWN WHITE OAK

RECLAIMED FLOORING – TIMBER FROM AGED STRUCTURES

The strength, durability, and availability of the massive Oak trees that populated the early American forests made it the go-to timber for barn and granary construction. The mighty Oak is as much a part of Americana as the barn itself. These planks are resawn from authentic reclaimed barn beams, resulting in cleaner, more uniform planks than that usual reclaimed Oak floor.

DISTINCTIVE ATTRIBUTES

Our Antique Appearance-Grade Resawn White Oak hardwood wide plank flooring features a moderate, authentic mix of sound checking, sound cracks, knots and insect holes/tracks, together with same strength, durability and wear-resistance as our other reclaimed Oak options.

ENGINEERED FLOORING SPECS:

Our reclaimed flooring designed for added stability - featuring real hardwood glued over a plywood core.

BOARD WIDTHS	3" to 12"
BOARD LENGTH	2' to 12'
PLANK THICKNESS	5/8" (3/4" & 11/16" available)
WEAR LAYER	4mm
PLYWOOD	8-ply Baltic Birch
FINISH OPTIONS	- prefinished**/unfinished - authentic hand-scrape - machine hand-scrape - wire brushing - end-matching to 12"

SOLID FLOORING SPECS:

Our reclaimed flooring is timber taken from old wooden structures such as barns and factory buildings.

BOARD WIDTHS	3" to 12"
BOARD LENGTH	2' to 12'
PLANK THICKNESS	3/4", 5/8", 1/2" (3/8"* & 11/16" available) (5/8" up to 8" only) (3/8", 1/2" up to 6" only)
FINISH OPTIONS	- prefinished**/unfinished - authentic hand-scrape - machine hand-scrape - wire brushing - end-matching to 12"

*3/8" solid flooring only available in widths of up to 6".

**Prefinish options are only available in plank thicknesses of 3/4", 5/8" and 11/16".

NOTE: Each of our flooring products possess unique characteristics and beauty. While our samples provide a close representation of each specie, they are for photo reference only and cannot exactly match the end product.

EDGE MILLING OPTIONS





specs as shown: solid, on-site sand with oil-based poly finish widths: 4" to 8" lengths: 2' to 12'

ANT. APPEARANCE-GRADE RESAWN WHITE OAK

